



CPA 451 & 452 Protective Covers


COMPAERO
India Pvt. Ltd.



CPA 451 - Plug Cover



CPA 452 - Receptacle Cover



CPA 451-13 W-S5-22

Compaero Identifier		Eyelet or Ring Size	See Page 9 Enter "00" for a lanyard and length as specified with no eyelet or ring attached (Suffix A for 30° Ring)
Series Identifier	451: D38999 SERIES 4 PLUG 452: D38999 SERIES 4 RECEPTACLE	Lanyard Length in Inches (0.25" Increments Only)	For 5 Inches use "5" For 4.5 Inches use "4.5" For 4.25 Inches use "4.25"
Shell Size		Lanyard Style	X - No accessory S - Stainless Steel Sash Chain G - Nylon Rope, Black GW - Nylon Rope, Green Y - Stainless Steel Wire Rope, Nylon Jacket T - Stainless Steel Wire Rope, Teflon Jacket R - Stainless Steel Wire Rope, PVC Jacket CF - Crimp Ferrule Option TR - Tie-Wrap Option B - Stainless Steel Bead Chain (See Page 8)
Finish & Material	See Page 5		

Table 1 CPA 451 Plug Cover Dimensions

SHELL SIZE	ØA MAX.		G MAX.		STD. LANYARD LENGTH*	
	in	mm	in	mm	in	mm
11	1.380	35.05	1.731	43.97	5.0	127.00
13	1.570	39.88	1.731	43.97	5.0	127.00
15	1.660	42.17	1.731	43.97	5.0	127.00
17	1.790	45.47	1.731	43.97	5.0	127.00
19	1.920	48.77	1.731	43.97	5.0	127.00
21	2.060	52.33	1.731	43.97	5.0	127.00
23	2.250	57.15	1.731	43.97	5.0	127.00
25	2.380	60.45	1.731	43.97	5.0	127.00

* Tolerances for lanyard Length
inches: ±.25
millimeters: ±6.35

Table 2 CPA 452 Receptacle Cover Dimensions

SHELL SIZE	ØB MAX.		J MAX.		STD. LANYARD LENGTH*	
	in	mm	in	mm	in	mm
11	1.047	26.59	1.375	34.93	5.0	127.00
13	1.220	30.99	1.375	34.93	5.0	127.00
15	1.346	34.19	1.375	34.93	5.0	127.00
17	1.472	37.39	1.375	34.93	5.0	127.00
19	1.583	40.21	1.375	34.93	5.0	127.00
21	1.705	43.31	1.375	34.93	5.0	127.00
23	1.831	46.50	1.375	34.93	5.0	127.00
25	1.957	49.71	1.375	34.93	5.0	127.00

* Tolerances for lanyard Length
inches: ±.25
millimeters: ±6.35

Lanyard Options

S-Stainless steel Sash chain




B-Stainless Steel Bead Chain




G-Nylon Rope, Black




CF-Crimp Ferrule Option



TR-Tie Wrap Option



X-No Accessory



Solid Rings





Table 4 Ring Specification

Ring	$\varnothing A$		Ring 30°	$\varnothing A$	
	in	mm		in	mm
20	.512	13.00	20A	.512	13.00
21	.591	15.01	21A	.591	15.01
22	.724	18.38	22A	.724	18.38
23	.787	20.00	23A	.787	20.00
24	.913	23.19	24A	.913	23.19
25	1.043	26.49	25A	1.043	26.49
26	1.193	30.30	26A	1.193	30.30
27	1.283	32.58	27A	1.283	32.58
28	1.437	36.49	28A	1.437	36.49
29	1.547	39.29	29A	1.547	39.29
30	1.689	42.90	30A	1.689	42.90
31	1.772	45.00	31A	1.772	45.00
32	1.890	48.00	32A	1.890	48.00
33	2.140	54.40	33A	2.140	54.40
34	2.406	61.10	34A	2.406	61.10
35	2.656	67.50	35A	2.656	67.50

Eyelet




Table 3 Eyelet Specifications

Eyelet	$\varnothing B$
00	No Eyelet or Ring
01	0.140
02	0.167
03	0.197
04	0.125
05	0.156
06	0.182
07	0.191
08	0.218